

Claims:

1 1. A system for executing application software on a operating system within a
2 secured run-time environment without affecting an application software resources of a client
3 computer, the system comprising:

4 an application wrapper, wherein said application wrapper shields the application software
5 resources, whereby said secured run-time environment for executing said application
6 software is created and the application software resources are protected; and

7 the application wrapper further comprising a privatized virtual file resource created from
8 an operating system file system, a privatized virtual registry created from an operating
9 system registry system, a privatized operating system shared component resource, a
10 privatized application configuration resource and a privatized environmental resources
11 for application variables.

12 2. The system of claim 1, wherein privatized virtual file resource further comprising:
13 intercepting file I/O request generated by one or more processes;

14 establishing a process ID for the intercepted file I/O request;

15 comparing process ID to establish operating system process and secured run-time
16 process;

17 establishing a process ID as operating system process and secured run-time process;

18 servicing the file I/O request for all process ID established as secured run-time process;

19 redirecting the file I/O request to operating system service for process ID established as
20 operating system process;

21 rejecting the file I/O request on secured run-time process resources for process ID
22 established as operating system process;

23 comparing process ID established as secured run-time process to further establish process
24 resources corresponding to process ID;

25 establishing corresponding process resources within secured run-time resources; and

26 rejecting the file I/O request on secured run-time process resources for process ID
27 established as secured run-time process and process ID belongs to other process
28 resources.

29 3. The system of claim 1, wherein privatized virtual registry further comprises:
30 privatizing virtual registry system by intercepting registry I/O request generated by
31 several process;
32 establishing process ID for the intercepted registry I/O request;
33 comparing process ID to establish operating system process and secured run-time
34 process;
35 establishing process ID as operating system process and secured run-time process;
36 servicing the registry I/O request for all process ID established as secured run-time
37 process;
38 redirecting the registry I/O request to operating system service for process ID established
39 as operating system process;
40 rejecting the registry I/O request on secured run-time process resources for process ID
41 established as operating system process;
42 comparing process ID established as secured run-time process to further establish process
43 resources corresponding to process ID;
44 establishing corresponding process resources within secured run-time resources; and

45 rejecting the registry I/O request on secured run-time process resources for process ID
46 established as secured run-time process and process ID belongs to other process resources.

47 4. The system of claim 1, wherein privatizing operating system shared component
48 resource further comprising:

49 searching secured application process for injecting component hooker;
50 checking the said secured application process to establish whether the process is injected
51 with component hooker;

52 establishing the said secured application process as new secured application process for
53 said secured application process not injected with component hooker;

54 injecting component hooker to new secured application process to intercept component
55 process;

56 repeating component hooker injection for all the new secured application process;

57 5. The system of claim 1, wherein privatizing operating system shared component
58 resource further comprising:

59 Initializing component redirection table to provide component redirecting information;

60 Registering virtual component required for the secured application;

61 Adding redirecting information to the said component redirection table for the execution
62 of each selected said secured run-time application;

63 Removing component redirecting information from the said component redirection table
64 for the termination of each said secured run-time application;

65 6. The system of claim 1, wherein privatizing operating system shared component
66 resource further comprising:

67 intercepting component process function for replacing component search path with
68 secured application resource path;

69 replacing component search path with private resource path to load the component from
70 the secured application resource path; and

71 creating new process for the intercepted component with the replaced secured application
72 resource path.

73 7. The system of claim 1, wherein privatizing operating system shared component
74 resource further comprising:

75 intercepting component call for replacing component registry path with the said
76 privatized virtual registry path;

77 searching component redirection table for the said component redirecting information;

78 replacing component registry path with the said privatized virtual registry path retrieved
79 from the said component redirection table;

80 returning the intercepted call to the requested call with the replaced secured application
81 registry path for addressing the component location from the privatized virtual registry
82 system and further the said component is addressed to load from the said privatized
83 virtual file system;

84 redirecting the said component call as it is to the requested call for the said component
85 call originated from non secured run-time application and for the said component call,
86 which do not have redirecting information in the said component redirection table.

87 8. The system of claim 1, wherein privatizing operating system shared component
88 resource further comprising:

89 intercepting the said RPC message call for replacing component information with
90 privatized virtual component information;

91 searching component redirecting information from the said component redirection table;

92 replacing RPC message with the said privatized virtual component information retrieved
93 from the said component redirection table;

94 returning the intercepted RPC message call to the requested call with the replaced
95 message;

96 continuing the RPC call to locate the privatized virtual component through SCM;

97 redirecting the said RPC message call as it is to the requested call for the said component
98 call originated from non secured run-time application and for the said component call,
99 which do not have redirecting information in the said component redirection table.

100 9. The system of claim 1, wherein privatized application configuration resource
101 further comprises:

102 monitoring file I/O request for configuration file to provide separate configuration file;

103 searching and retrieving configuration file from secured application resources; and

104 serving application configuration file to requesting process.

105 10. The system of claim 1, wherein privatized environmental resources further
106 comprises:

107 intercepting environment variable request to supply private values to secured application
108 process;

109 verifying process ID to establish the process ID as operating system process or secured
110 application process;

111 redirecting the call for process ID established as operating system process;

112 reading variable data from secured application resource and returning the value to
113 requested process for read variable calls requested by the secured application process;

114 searching the requesting write variable in secured application resource to find the
115 presence of requesting write variable;

116 creating variable with variable data within secured application resource and returning the
117 status to requested process for variable do not exist in secured application resource; and
118 updating variable with variable data within secured application resource and returning the
119 status to requested process for variable exist in secured application resource.

120 11. The system of claim 1, wherein the application wrapper further comprises
121 selectively allowing the application software to interact operating system resources directly
122 during the said application software executing under the said secured run-time environment.

123 12. The system of claim 1, wherein the application wrapper further comprises
124 selectively allowing said application software to interact with other application software
125 resources directly during the said application software executing under the said secured run-time
126 environment.

127 13. The system of claim 1, wherein said application wrapper further comprises
128 providing a run-time environment to said application software that is visible to an operating
129 system run-time environment without having said application software run-time resources,
130 whereby said application software resources is simulated to said secured run-time environment
131 during the execution of said application software.

132 14. The system of claim 13, further comprising means for protecting the behavior of
133 said application software from other application and said operating system.

134 15. The system of claim 13, further comprising means for eliminating said application
135 conflicts from other running application software.

136 16. The system of claim 13, further comprising means for executing multiple instance
137 of single said application software.

138 17. The system of claim 1, wherein the said application wrapper further comprising
139 maintaining the application software resources away from said operating system resources,
140 whereby said operating system resources is protected from said application software resources.

141 18. The system of claim 1, wherein said application wrapper further comprises
142 permitting full access to said application software that requires to access for variation occurs to
143 said application software resources within the said application wrapper.

144 19. The system of claim 18 further comprising means for keeping the state of secured
145 run-time environment to said application software.

146 20. The system of claim 18, further comprising means for updating said application
147 software resources required by said application software.

148 21. The system of claim 1, wherein the said application wrapper monitors the said
149 application run-time request to determine the required said application software resources for
150 execution.

151 22. The system of claim 21, further comprising means for receiving said application
152 software resources to execute said application software in the said secured run-time environment.

153 23. The system of claim 21, further comprising means for incrementally executing the
154 said application software in the secured run-time environment.

155 24. A method for executing application software on a operating system within a
156 secured run-time environment without affecting an application software resources of a client
157 computer, the client compute comprising an application wrapper, wherein said application
158 wrapper shields the said application software resources, whereby a said secured run-time

environment for executing an said application software is created and the said application software resources is protected, the method further comprising:

privatizing virtual file resource created from an operating system file system;

privatizing virtual registry created from an operating system registry system;

privatizing operating system shared component resource;

privatizing application configuration resource; and

privatizing environmental resources for application variables.

25. The method of claim 24, wherein privatizing the virtual file resource further comprising:

intercepting file I/O request generated by several processes;

establishing process ID for the intercepted file I/O request;

comparing process ID to establish operating system process and secured run-time process;

establishing process ID as operating system process and secured run-time process;

servicing the file I/O request for all process ID established as secured run-time process;

redirecting the file I/O request to operating system service for process ID established as operating system process;

rejecting the file I/O request on secured run-time process resources for process ID established as operating system process;

comparing process ID established as secured run-time process to further establish process resources corresponding to process ID;

establishing corresponding process resources within secured run-time resources; and

rejecting the file I/O request on secured run-time process resources for process ID established as secured run-time process and process ID belongs to other process resources.

184 26. The method of claim 24, wherein Privatizing the virtual registry further
185 comprising:

186 privatizing virtual registry system by intercepting registry I/O request generated by
187 several process;

188 establishing process ID for the intercepted registry I/O request;

189 comparing process ID to establish operating system process and secured run-time
190 process;

191 establishing process ID as operating system process and secured run-time process;

192 servicing the registry I/O request for all process ID established as secured run-time
193 process;

194 redirecting the registry I/O request to operating system service for process ID established
195 as operating system process;

196 rejecting the registry I/O request on secured run-time process resources for process ID
197 established as operating system process;

198 comparing process ID established as secured run-time process to further establish process
199 resources corresponding to process ID;

200 establishing corresponding process resources within secured run-time resources; and

201 rejecting the registry I/O request on secured run-time process resources for process ID
202 established as secured run-time process and process ID belongs to other process
203 resources.

204 27. The method of claim 24, wherein privatizing operating system shared component
205 resource further comprising:

206 intercepting component process function for replacing component search path with
207 secured application resource path;

208 replacing component search path with private resource path to load the component from
209 the secured application resource path; and

210 creating new process for the intercepted component with the replaced secured application
211 resource path.

212 28. The method of claim 24, wherein privatizing operating system shared component
213 resource further comprising:

214 searching secured application process for injecting component hooker;

215 checking the said secured application process to establish whether the process is injected
216 with component hooker;

217 establishing the said secured application process as new secured application process for
218 said secured application process not injected with component hooker;

219 injecting component hooker to new secured application process to intercept component
220 process;

221 repeating component hooker injection for all the new secured application process;

222 29. The method of claim 24, wherein privatizing operating system shared component
223 resource further comprising:

224 Initializing component redirection table to provide component redirecting information;

225 Registering virtual component required for the secured application;

226 Adding redirecting information to the said component redirection table for the execution
227 of each selected said secured run-time application;

228 Removing component redirecting information from the said component redirection table
229 for the termination of each said secured run-time application;

230 30. The method of claim 24, wherein privatizing operating system shared component
231 resource further comprising:

232 intercepting component call for replacing component registry path with the said
233 privatized virtual registry path;

234 searching component redirection table for the said component redirecting information;

235 replacing component registry path with the said privatized virtual registry path retrieved
236 from the said component redirection table;

237 returning the intercepted call to the requested call with the replaced secured application
238 registry path for addressing the component location from the privatized virtual registry
239 system and further the said component is addressed to load from the said privatized
240 virtual file system;

241 redirecting the said component call as it is to the requested call for the said component
242 call originated from non secured run-time application and for the said component call,
243 which do not have redirecting information in the said component redirection table.

244 31. The method of claim 24, wherein privatizing operating system shared component
245 resource further comprising:

246 intercepting the said RPC message call for replacing component information with
247 privatized virtual component information;

248 searching component redirecting information from the said component redirection table;

249 replacing RPC message with the said privatized virtual component information retrieved
250 from the said component redirection table;

251 returning the intercepted RPC message call to the requested call with the replaced
252 message;

253 continuing the RPC call to locate the privatized virtual component through SCM;

254 redirecting the said RPC message call as it is to the requested call for the said component
255 call originated from non secured run-time application and for the said component call,
256 which do not have redirecting information in the said component redirection table.

257 32. The method of claim 24, wherein privatizing application configuration resource
258 further comprising:

259 monitoring file I/O request for configuration file to provide separate configuration file;

260 searching and retrieving configuration file from secured application resources; and

261 serving application configuration file to requesting process.

262 33. The method of claim 24, wherein privatizing environmental resources for
263 application variables further comprising:

intercepting environment variable request to supply private values to secured application process;

verifying process ID to establish the process ID as operating system process or secured application process;

redirecting the call for process ID established as operating system process;

reading variable data from secured application resource and returning the value to requested process for read variable calls requested by the secured application process;

searching the requesting write variable in secured application resource to find the presence of requesting write variable;

creating variable with variable data within secured application resource and returning the status to requested process for variable do not exist in secured application resource; and

updating variable with variable data within secured application resource and returning the status to requested process for variable exist in secured application resource.

34. The method of claim 24, wherein selectively allows said application software to interact operating system resources directly during the said application software executing under the said secured run-time environment.

35. The method of claim 24, wherein selectively allows said application software to interact with other application software resources directly during the said application software executing under the said secured run-time environment.

36. The method of claim 24, wherein said application wrapper provides an run-time environment to said application software that visible to be an operating system run-time environment without having said application software run-time resources, whereby said application software resources is simulated to said secured run-time environment during the execution of said application software.

37. The method of claim 36, further comprising protecting the behavior of said application software from other application and said operating system.

38. The method of claim 36, further comprising eliminating said application conflicts from other running application software.

292 39. The method of claim 36, further comprising executing multiple instance of single
293 said application software.

294 40. The method of claim 24, wherein the said application wrapper keeps the
295 application software resources away from said operating system resources, whereby said
296 operating system resources is protected from said application software resources.

297 41. The method of claim 24, wherein said application wrapper allows full access to
298 said application software that requires to access for variation occurs to said application software
299 resources within the said application wrapper.

300 42. The method of claim 41, further comprising a means for keeping the state of
301 secured run-time environment to said application software.

302 43. The method of claim 41, further comprising a means for updating said application
303 software resources required by said application software.

304 44. The method of claim 24, wherein the said application wrapper monitors the said
305 application run-time request to determine the required said application software resources for
306 execution.

307 45. The method of claim 44, further comprising a means for receiving said
308 application software resources to execute said application software in the said secured run-time
309 environment.

310 46. The method of claim 44, further comprising a means for incrementally executing
311 the said application software in the secured run-time environment.